

**tyco** | Software House

# C•CURE 9000 v2.80

## Security and Event Management System



### Key features

- OSDP support for reader to panel communications on iSTAR Ultra Series controllers
- Supports up to 5,000 readers per single server and 40 Satellite Application Server scalability for Enterprise systems
- Enterprise system remains operational throughout upgrade process with multiversion software support
- Access to C•CURE 9000 from any Internet browser with C•CURE Web
- Administer and monitor C•CURE 9000 from your mobile device with C•CURE Go
- Software House Connected Partner Program for standards-based integrations
- Part of the Cyber Protection Program reducing the risk of vulnerabilities

### Powerful and Flexible Security Management

Software House C•CURE 9000 is one of the industry's most powerful and flexible security management systems. Monitor events, manage personnel, create reports, display dynamic views, monitor system activity, view video and manage visitors anywhere in the world directly from your PC using the full C•CURE client, the web client or on the move with C•CURE Go mobile app.

### Information and Event Management at its Best

Describing C•CURE 9000 as an access control system is an enormous understatement. The way in which you are able to manage credentials and privileges is what sets C•CURE 9000 apart.

- Area Control and Occupancy Management allow you to enforce global anti-passback, define occupancy restrictions and lock down procedures in sensitive or classified areas
- Intrusion Zones and Keypad Commands provide additional verification requirements and duress triggers
- Dynamic Views and Editable Maps serve up critical information in a customizable way, all while allowing you to find, manage, and acknowledge significant incidents on user-defined floor plans
- Visitor Management portal gives you control of creating and managing visitor appointments

## Information and Event Management at its Best (Continued)

- Access Management offers a 24/7 solution for managing cardholder access requests without requiring direct involvement from the security team
- Intuitive badging and smart card enrollment
- Unified Access Control and Video experience

As an option, you can take a holistic video approach of managing access control, video, and intrusion with a deeply embedded victor unifying client. This flexibility, coupled with the system's powerful distributed architecture, makes C•CURE 9000 the leader in providing solutions to some of the most complex security challenges in mid to large enterprise applications.

### Mastering Scalability

C•CURE 9000 provides the ultimate in scalability from a single server supporting up to 5,000 readers and 500,000 credentials to an advanced distributed enterprise architecture that supports a master and up to 40 satellite application servers. Whether your organization consists of one facility with a few doors or many that span the globe, this solution scales as your company grows.

### Industry's Most Robust Integrations

C•CURE 9000 brings you a myriad of integrated solutions including video, intrusion, intercom, fire alarm management, PSIM and more. The integrations are thoroughly tested and delivered to you through the intuitive C•CURE 9000 interface.

### Enterprise Architecture

The C•CURE 9000 Enterprise architecture supports one master application server (MAS) and up to 40 satellite application servers (SAS) for enterprise scalability up to 200,000 readers and 500,000 credentials managed under one system for management, monitoring and reporting.

Corporate security personnel and IT managers receive central control over the entire system, while each local facility maintains control of its individual operation. Each SAS may be positioned close to its relevant field hardware – reducing traffic to the MAS and optimizing performance. Each facility maintains a local SQL database which is synchronized with the MAS for global control and reporting. The MAS distributes these changes globally from each independent SAS, which ensures all servers are equipped and operating with up-to-date information.

By connecting a SAS to the LAN with local access control hardware, alarm monitoring and badging workstations, local performance is optimized versus the latency you may experience from the WAN. Local performance is further optimized since the MAS performs all global reporting across all SASs, thus allowing each SAS to allocate its resources solely to important access control functions.

### Independent Control

Each SAS communicates directly with the MAS but is not dependent on the MAS for access control. Each satellite system administrator has total control over all access control field hardware and system information related to his/her respective location. This gives regional system administrators autonomous control over their individual regions independent of the MAS and corporate WAN.

### Central Alarm Monitoring and Management

C•CURE 9000 Enterprise allows you to simultaneously monitor alarms from multiple locations at one convenient workstation. Viewing all data across all SASs gives you a full view of your entire operation. Monitoring of alarms from multiple sites means operators may rotate the responsibility whether from different buildings at a campus to different locations across the globe.

### Global Reporting

With C•CURE 9000 Enterprise's global reporting functionality, you can retrieve personnel, configuration, hardware, journal, audit and more data from all facilities within the organization. This saves valuable time searching for data and compiling critical reports since all global information is replicated on the MAS.

## C•CURE 9000 Standalone and Enterprise System Capacities

C•CURE 9000 MAS Values (Default/Maximum) <sup>1</sup>						
	MAS1	MAS2	MAS3	MAS4	MAS5	MAS6
Enabled Global Personnel Records <sup>2</sup>	1k	10k	25k	100k	250k	500k
Simultaneous Clients <sup>3</sup>	5/100	5/100	5/100	10/100	10/100	10/100
Badging Clients	1/100	1/100	1/100	2/100	2/100	2/100

C•CURE 9000 Standalone and SAS Values (Default/Maximum) <sup>4</sup>										
	L <sup>5</sup>	M <sup>5</sup>	N <sup>5</sup>	P <sup>6</sup>	Q <sup>6</sup>	R <sup>6</sup>	PLUS <sup>6</sup>	S <sup>6</sup>	S Plus <sup>6</sup>	T <sup>6</sup>
Online Readers	16	32	64	128	256	512	1,000	2,500	3,500	5,000
C•CURE Go Reader (Mobile)	0/10	0/10	0/10	0/30	0/30	0/30	0/30	0/30	0/30	0/30
Online Inputs	1k	1k	1k	5k/10k	5k/10k	5k/10k	5k/10k	10k	15k	20k
Online Outputs	1k	1k	1k	5k/10k	5k/10k	5k/10k	5k/10k	10k	15k	20k
Enabled Personnel Records	7k	12k	40k	45k	250k	250k	250k	500k	500k	500k
Concurrent Clients <sup>3</sup>	10/30	10/30	10/30	20/256	30/256	40/256	80/256	100/256	100/256	100/256
Concurrent Badging Clients	1/30	1/30	1/30	2/256	2/256	3/256	5/256	10/256	10/256	10/256

<sup>1</sup> Additional clients and badging clients may be added to a system license. Simultaneous client connections are tabulated by C•CURE 9000 Administration, Alarm Monitoring, and Web Client connections. C•CURE 9000 is designed to be flexible and allow for expansion. The 100 is a design capability while the tested limit is 10. System performance will vary depending upon specific hardware configuration including number of communication lines/ports, download/upload frequency, etc.

<sup>2</sup> Global personnel records are the maximum supported as an aggregate across the total number of SAS servers in addition to the SAS server local personnel records.

<sup>3</sup> Client License – Single monitoring station application, administration application or web client application.

<sup>4</sup> Additional simultaneous clients, badging clients, inputs/outputs may be purchased separately. Simultaneous client connections are tabulated by C•CURE 9000 Administration, Alarm Monitoring, and Web Client connections. C•CURE 9000 is designed to be flexible and allow for expansion. The 256 is a design capability while the tested limit is 100. System performance will vary depending upon specific hardware configuration including number of communication lines/ports, download/upload frequency, etc.

<sup>5</sup> The baseline capabilities of the system are within the envelope of operation for utilization of SQL Express.

<sup>6</sup> (SQL and SQL Express): An SQL Express license is shipped with every system software DVD package. Series P through S require a full SQL Server Standard or Enterprise (64-bit) license which may be purchased separately.

## Specifications

C•CURE 9000 Client Workstation	
Recommended Hardware and Software	
Processor	Intel Core i5-3470 (6 MB, 3.2 GHz or greater)
Hard Disk Drive	500 GB or greater
Drive Speed	7,200 RPM or greater
Memory	8GB or greater
Network Adapter Card	Integrated Gigabit Network Port
DVD Drive	Recommended
Client Video Card	2GB NVIDIA Quadro K620

Operating System Support	Windows 7 SP1 Professional & Enterprise (64-bit) Windows 8.1 SP1 Professional & Enterprise (64-bit) Windows 10 Professional & Enterprise (64-bit) Windows Server 2012 R2 Standard SP1 (64-bit) Windows Server 2016 Standard & Enterprise (64-bit) Windows Server 2019 (64-bit)
--------------------------	---

C•CURE 9000 Standalone Server Series L, M, N	
Recommended Hardware and Software	
Processor	Intel® 3rd Generation Core i7-3770 or greater (8 MB, 3.4 GHz or greater)
Hard Disk Drives	Dual drives: primary drive = 1TB or greater (9000 Runtime); secondary drive = 1TB or greater (data backups). SSD is recommended
Drive Speed	7,200 RPM or greater
Memory	16GB or greater
Network Adapter Card	Integrated Gigabit Network Port
DVD Drive	Recommended
Video Card	Integrated Video Subsystem (dedicated video accelerator recommended when used as a client workstation)
Database Support (English Only)	SQL Server 2012 (SP3 or later) Express/Standard/Enterprise (64-bit, SP2 or later) SQL Server 2014 (SP1 or later) Express/Standard/Enterprise (64-bit) SQL Server 2016 Express/Standard/Enterprise (64-bit) SQL Server 2017 Express, Standard, Enterprise (Express)
Operating System Support	Windows 7 Professional & Enterprise SP1 or later (64-bit) Windows 8.1 Professional & Enterprise SP1 or later (64-bit) Windows 10 Professional & Enterprise (64-bit) Windows Server 2012 R2 SP1 Standard & Data Center (64-bit) Windows Server 2016 Standard & Enterprise (64-bit) Windows Server 2019 (64-bit) If you plan to install C•CURE Web on the same PC with the C•CURE 9000 server, you must use Windows 8.1 SP1 or later.
Web Server	IIS V8.0 or higher for C•CURE Web, C•CURE Go and victor Web Service

Note: IIS v8.0 is required to install C•CURE Web on the same machine as C•CURE 9000 Classic Web Client (Classic), C•CURE Go, victor Web Service or C•CURE Mobile. Windows 7 and Windows 8.1 do not support IIS v8.0.

C•CURE 9000 Standalone Server Series P, Q, R, R+, S, S+, T SAS Server Series L, M, N	
Recommended Hardware and Software	
Processor	Intel Xeon E3-1240 v5 (3.5 GHz or greater)
Hard Disk Drives	Dual drives: primary drive = 1TB or greater (9000 Runtime); secondary drive = 1TB or greater (data backups). SSD is recommended.
Drive Speed	15,000 RPM or greater
Memory	32GB or greater
Network Adapter Card	Intel Gigabit ET Quad Port Adapter, Gigabit Ethernet NIC, PCIe x4
DVD Drive	Recommended
Video Card	Integrated video subsystem (dedicated video accelerator recommended when used as a client workstation)
Database Support (English Only)	SQL Server 2012 Standard & Enterprise (64-bit) SQL Server 2014 Standard & Enterprise (64-bit) SQL Server 2016 Standard & Enterprise (64-bit) SQL Server 2017 Standard & Enterprise (64-bit)
Operating System Support	Windows Server 2012 R2 Standard SP1 & Data Center (64-bit) Windows 10 Professional & Enterprise (64-bit) Windows Server 2016 Standard & Enterprise (64-bit) Windows Server 2019 Standard & Enterprise (64-bit)
Web Server	IIS V8.0 or higher for C•CURE Web, C•CURE Go and victor Web Service

Note: IIS v8.0 is required to install C•CURE Web on the same machine as C•CURE 9000 Classic Web Client (Classic), C•CURE Go, victor Web Service or C•CURE Mobile

### C•CURE 9000 SAS Server Series P, Q, R, R+, S, S+, T MAS Server

Recommended Hardware and Software	
Processor	Intel Xeon E5-2630 v4 (2.2 GHz or greater)
Hard Disk Drives	Dual drives: primary drive = 1TB or greater (9000 Runtime); secondary drive = 1TB or greater (data backups). SSD is recommended.
Drive Speed	15,000 RPM or greater
Memory	32GB Minimum
Network Adapter Card	Intel Gigabit ET Quad Port Adapter, Gigabit Ethernet NIC, PCIe x4
DVD Drive	Recommended
Video Card	Integrated Video Subsystem <sup>6</sup>
Database Support (English Only)	SQL Server 2012 Standard & Enterprise (64-bit) SQL Server 2014 (SP1 or later) Standard/Enterprise (64-bit) SQL Server 2016 Standard/Enterprise (64-bit) SQL Server 2017 Standard/Enterprise (64-bit)
Operating System Support	Windows Server 2012 R2 SP1 Standard & Data Center (64-bit) Windows Server 2016 Standard & Enterprise (64-bit) Windows Server 2019 Standard & Enterprise (64-bit)
Web Server	IIS V8.0 or higher for C•CURE Web, C•CURE Go and victor Web Service

Note: IIS V7.0 or higher for C•CURE 9000 Web Client (Classic), C•CURE Go and victor Web Service

Maximum Concurrent SAS per MAS	40
Authentication	Windows Authentication on Domain and Trusted Domain
Supported Languages <sup>7</sup>	Arabic, Brazilian Portuguese, Czech, Danish, Dutch, English, French, German, Hungarian, Italian, Japanese, Korean, Polish, Russian, Simplified Chinese, Spanish, Swedish, Traditional Chinese and Turkish

<sup>6</sup> For multiple screen display or other display applications, additional video cards required.

<sup>7</sup> Languages supported with English OS with language pack, not native OS.

Note: C•CURE 9000 has limited performance and support on 32-bit OS platforms (with 4GB memory limitation) with a minimum requirement of 4GB memory. For latest supported Service Pack for OS/DB, please consult the C•CURE 9000 version specific release notes. SQL Server 2014 Express will be the default install for C•CURE 9000 v2.80. All SQL Server compatibility needs to be verified with TD encryption mode

### New Features in C•CURE 9000 v2.80

Tag objects within C•CURE 9000 using metatags to easily find, manage, and organize your system
Rapidly retrieve queried results on names, types, and tags throughout C•CURE 9000 with Smart Search
Using Security View perform automatic device-to-video mapping to view devices and associated video closest to an alarm/incident, map the location, and process the incident from one intuitive screen saving on configuration time
Quickly launch the new Event Assessment Application layout with the click of a button - no programming required
Add GIS pins for any objects such as Doors, Readers, Events, Inputs, and Outputs on maps to broaden search capabilities by location
Quickly verify personnel identity using Duo two-factor authentication mobile app before granting access on existing iSTAR doors without the need to update hardware

---

#### About Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit [www.swhouse.com](http://www.swhouse.com) or follow **Software House** on LinkedIn, Twitter, and Facebook.

© 2021 Johnson Controls. All Rights Reserved.

All trademarks are the property of their respective owners. Product offerings and specifications are subject to change without notice.

Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

SH0241-DS-202106-R11-HS-EN